NSN 5955-00-925-9406

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-925-9406

Overall Length:					
1.023 inches					
Terminal Length:					
Between 0.223 inches and 0.248 inches					
Overall Width:					
0.757 inches					
Body Length:					
0.775 inches					
Body Width:					
0.725 inches					
Body Thickness:					
0.317 inches					
Overall Thickness:					
0.352 inches					
Terminal Diameter:					
Between 0.048 inches and 0.052 inches					
Mode Of Oscillation:					
Fundamental					
Circuit Resonance:					
Antiresonance					
Load Capacitance In Picofarads:					
Between 31.5 and 32.5					
Shunt Capacitance In Picofarads:					
7.0					
Specified Frequency:					
9.55556 megahertz					
Frequency Tolerance At Reference Tempurature In Percent:					
-0.007/+0.007					
Frequency Stability In Percent:					
-0.0005/+0.0005					
Controlled Reference Temp:					
75.0 degrees celsius					
Operable Tempurature Range:					
-55.0/+90.0 degrees celsius					
Holder Cover Material:					
Metal					
Operating Tempurature Range:					
+70.0/+80.0 degrees celsius					
Center To Center Distance Between Terminals:					
0.478 mils and 0.494 centimeters					
Drive Level Rating:					

brive Level Rating

Between 4.0 milliwatts and 6.0 milliwatts

NSN 5955-00-925-9406

Quartz Crystal Unit - Page 2 of 2



	Talawanaa Far	0	T	In Danasat.
-requency	Tolerance For	Operating	rempurature	in Percent:

-0.002/+0.002

Equivalent Resistance Value In Ohms:

35.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098-9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0