Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-930-5194

| Overall Length: |
|---|
| 4.600 inches |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 2.000 inches |
| Environmental Protection: |
| Shock resistant and vibration |
| Vibration Resistance Range In Hertz: |
| Not rated |
| Shock Resistance Rating In Gravitational Units: |
| Not rated |
| Operating Tempurature Range: |
| -55.0/+60.0 degrees celsius |
| Average Life Measurement: |
| Not rated |
| Basic Shape Style: |
| Rectangular or square |
| Identification Designator: |
| 14844-fe 20-pc |
| Maximum Operating Altitude Rating: |
| Not rated |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Circuit Construction Type: |
| Solid state |
| Frequency Per Channel: |
| 1.0 megahertz output channel |
| Attenuation In Decibels: |
| Not rated |
| Average Power Rating Per Channel: |
| 17.0 watts input |
| Signal Voltage Rating Per Channel: |
| 28.000 volts input |
| Overall Gain: |
| Not rated |
| Impedance Rating Per Channel: |
| Not rated |
| |
| |

Crystal Controlled Oscillator - Page 2 of 2



Maximum Continuous Operating Time In Hours: Not rated **Connection Type And Location:** Receptacle, power bottom **Operating Ac Frequency In Hertz:** 60.0 single voltage **Connection Contact Type And Quantity:** 8 receptacle, power external **External Dc Operating Voltage In Volts:** 13.1 single voltage err-100 **External Ac Operating Voltage In Volts:** 120.0 single voltage Phase: Single Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A32200