## NSN 5955-00-930-6059

Quartz Crystal Unit - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5955-00-930-6059

0.775 inches
Terminal Length:
1.500 inches
Overall Width:
0.757 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.028 inches and 0.032 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 21.0 and 22.0
Specified Frequency:
490.000 kilohertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.001/+0.001
Frequency Stability In Percent:
-0.0005/+0.0005
Controlled Reference Temp:
75.0 degrees celsius
Operable Tempurature Range:
-40.0/+70.0 degrees celsius
Holder Cover Material:
Metal
Operating Tempurature Range:
+70.0/+80.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.001/+0.001
Equivalent Resistance Value In Ohms:

2500.0

## NSN 5955-00-930-6059

Quartz Crystal Unit - Page 2 of 2



Style	Desia	nator:

Oval body, wire leads

## **Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/79 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0