NSN 5955-00-930-6060

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-930-6060

Overall Length:

0.775 inches

Terminal Length:

1.500 inches

Overall Width:

0.757 inches

Body Width:

0.725 inches

Body Thickness:

0.317 inches

Overall Thickness:

0.352 inches

Terminal Diameter:

Between 0.028 inches and 0.032 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

Between 21.0 and 22.0

Specified Frequency:

495.000 kilohertz

Frequency Tolerance At Reference Tempurature In Percent:

-0.001/+0.001

Frequency Stability In Percent:

-0.0005/+0.0005

Controlled Reference Temp:

75.0 degrees celsius

Operable Tempurature Range:

-40.0/+70.0 degrees celsius

Holder Cover Material:

Metal

Operating Tempurature Range:

+70.0/+80.0 degrees celsius

Center To Center Distance Between Terminals:

0.478 mils and 0.494 centimeters

Drive Level Rating:

Between 1.6 milliwatts and 2.4 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001

Equivalent Resistance Value In Ohms:

2500.0

NSN 5955-00-930-6060

Quartz Crystal Unit - Page 2 of 2



Style Designator:

Oval body, wire leads

Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/79 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A059a0