# -6062



p.com/nsn/5955-00-930-6062

<b>NSN 5955-00-930-6062</b> Quartz Crystal Unit - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5955-00-930-60
Overall Length:
0.775 inches
Terminal Length:
Between 1.500 inches and 1.525 inches
Overall Width:
0.757 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.028 inches and 0.032 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 21.0 and 22.0
Specified Frequency:
510.000 kilohertz
Frequency Stability In Percent:
-0.0005/+0.0005
Controlled Reference Temp:
75.0 degrees celsius
Operable Tempurature Range:
-40.0/+70.0 degrees celsius
Holder Cover Material:
Metal or glass
Operating Tempurature Range:

### **Center To Center Distance Between Terminals:**

0.478 mils and 0.494 centimeters

#### **Drive Level Rating:**

Between 1.6 milliwatts and 2.4 milliwatts

### Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001 and -0.003/+0.003

## Equivalent Resistance Value In Ohms:

2500.0

Style Designator:

Rectangular body, gull wing

# NSN 5955-00-930-6062

Quartz Crystal Unit - Page 2 of 2



## Test Data Document:

81349-milc3098-50 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0