NSN 5955-00-934-8853

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-934-8853

Overall Length:
0.775 inches
Terminal Length:
0.500 inches
Overall Width:
0.757 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.032 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
32.0
Specified Frequency:
opcomou i requency.
1.2375 megahertz
1.2375 megahertz
1.2375 megahertz Holder Cover Material:
1.2375 megahertz Holder Cover Material: Metal
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 400.0
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 400.0 Style Designator:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 400.0 Style Designator: Oval body, wire leads
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 400.0 Style Designator: Oval body, wire leads Shelf Life:
1.2375 megahertz Holder Cover Material: Metal Operating Tempurature Range: -55.0/+71.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 400.0 Style Designator: Oval body, wire leads Shelf Life: N/a

Demilitarization:

Yes - demil/mli

NSN 5955-00-934-8853

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0