## NSN 5955-00-942-6812

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-942-6812

| Overall Length:   |
|---|
| 1.806 inches  |
| Terminal Length:  |
| 0.244 inches  |
| Overall Width:  |
| 0.757 inches  |
| Body Length:  |
| 1.562 inches  |
| Body Width:   |
| 0.725 inches  |
| Body Thickness:   |
| 0.317 inches  |
| Overall Thickness:  |
| 0.352 inches  |
| Terminal Diameter:  |
| Between 0.048 inches and 0.052 inches                     |
| Mode Of Oscillation:                                      |
| Fundamental   |
| Circuit Resonance:  |
| Series resonance  |
| Shunt Capacitance In Picofarads:                          |
| 10.4  |
| Specified Frequency:                                      |
| 182.340 kilohertz   |
| Holder Cover Material:                                    |
| Metal   |
| Operating Tempurature Range:                              |
| -5.0/+90.0 degrees celsius                                |
| Fragility Factor:   |
| Moderately rugged   |
| Center To Center Distance Between Terminals:              |
| 0.478 mils and 0.494 centimeters                          |
| Drive Level Rating:                                       |
| Between 15.0 microwatts and 50.0 microwatts               |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.020/+0.020   |
| Equivalent Resistance Value In Ohms:                      |
| 4000.0  |
| Style Designator:   |
| Oval body, pin terminals                                  |
| Fsc Application Data:                                     |
| Ossillators and nisma algoritis amost !-                  |

Oscillators and piezoelectric crystals

## NSN 5955-00-942-6812

Quartz Crystal Unit - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0