## NSN 5955-00-942-9830

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-942-9830

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
39.82222 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.007/+0.007
-0.007/+0.007  Frequency Stability In Percent:
Frequency Stability In Percent:
Frequency Stability In Percent: -0.00025/+0.00025
Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp:
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range:
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material:
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material:  Metal
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material:  Metal  Operating Tempurature Range:
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material: Metal  Operating Tempurature Range: +70.0/+80.0 degrees celsius
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material: Metal  Operating Tempurature Range: +70.0/+80.0 degrees celsius  Center To Center Distance Between Terminals:
Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 75.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material: Metal  Operating Tempurature Range: +70.0/+80.0 degrees celsius  Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters

-0.001/+0.001

## NSN 5955-00-942-9830

Quartz Crystal Unit - Page 2 of 2



<b>Equivalent Resistance</b>	Value In	Ohms:
------------------------------	----------	-------

40.0

**Style Designator:** 

Oval body, pin terminals

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0