NSN 5955-00-944-9326

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-944-9326

View Online at https://aerobasegroup.com/nsn/5955-00-944-9326
Overall Length:
Between 0.505 inches and 0.525 inches
Terminal Length:
Between 0.630 inches and 0.642 inches
Overall Width:
Between 0.408 inches and 0.428 inches
Body Width:
Between 0.380 inches and 0.402 inches
Body Thickness:
Between 0.156 inches and 0.176 inches
Overall Thickness:
Between 0.096 inches and 0.116 inches
Terminal Diameter:
Between 0.016 inches and 0.019 inches
Mode Of Oscillation:
Fifth overtone and third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
Between 5.0 and 6.5
Specified Frequency:
54.500 megahertz
Holder Cover Material:
Metal or glass
Operating Tempurature Range:
-40.0/+90.0 degrees celsius and -55.0/-40.0 degrees celsius and +90.0/+105.0 degrees celsius
Center To Center Distance Between Terminals:
0.184 mils and 0.200 centimeters
Drive Level Rating:
2.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.0025/+0.0025 and -0.005/+0.005
Equivalent Resistance Value In Ohms:
50.0
Style Designator:
Rectangular body, gull wing
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5955-00-944-9326

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0