NSN 5955-00-945-1620

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-945-1620

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.505 inches and 0.525 inches

**Terminal Length:** 

Between 0.630 inches and 0.642 inches

Overall Width:

Between 0.408 inches and 0.428 inches

**Body Width:** 

Between 0.380 inches and 0.402 inches

**Body Thickness:** 

Between 0.156 inches and 0.176 inches

**Overall Thickness:** 

Between 0.096 inches and 0.116 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

**Mode Of Oscillation:** 

Fifth overtone and third overtone

**Circuit Resonance:** 

Series resonance

**Shunt Capacitance In Picofarads:** 

Between 5.0 and 6.5

**Specified Frequency:** 

51.500 megahertz

**Holder Cover Material:** 

Metal or glass

**Operating Tempurature Range:** 

-50.0/+90.0 degrees celsius

**Center To Center Distance Between Terminals:** 

0.184 mils and 0.200 centimeters

**Drive Level Rating:** 

2.0 milliwatts

**Frequency Tolerance For Operating Tempurature In Percent:** 

-0.0025/+0.0025 and -0.005/+0.005

**Equivalent Resistance Value In Ohms:** 

50.0

**Style Designator:** 

Rectangular body, gull wing

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

Yes - demil/mli

## NSN 5955-00-945-1620

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0