## NSN 5955-00-945-1730

Quartz Crystal Unit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-00-945-1730         |
|---|
| Overall Length:   |
| 1.874 inches  |
| Terminal Length:  |
| 0.238 inches  |
| Overall Width:  |
| 0.757 inches  |
| Body Length:  |
| 1.526 inches  |
| Body Width:   |
| 0.725 inches  |
| Body Thickness:   |
| 0.317 inches  |
| Overall Thickness:  |
| 0.352 inches  |
| Terminal Diameter:  |
| 0.050 inches  |
| Mode Of Oscillation:  |
| Fundamental   |
| Circuit Resonance:  |
| Antiresonance   |
| Load Capacitance In Picofarads:                                       |
| Between 19.5 and 20.5   |
| Shunt Capacitance In Picofarads:                                      |
| Between 4.0 and 5.4   |
| Specified Frequency:  |
| 61.000 kilohertz  |
| Holder Cover Material:  |
| Metal or glass  |
| Operating Tempurature Range:  |
| -40.0/+70.0 degrees celsius   |
| Center To Center Distance Between Terminals:                          |
| 0.486 inches  |
| Drive Level Rating:   |
| Between 0.1000 milliwatts and 0.0999 milliwatts and 0.1001 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent:             |
| -0.012/+0.012 and -0.050/+0.050                                       |
| Equivalent Resistance Value In Ohms:                                  |
| 100000.0  |
| Style Designator:   |
| Tube body, wire leads   |
| Test Data Document:   |

81349-milc3098/55 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-00-945-1730

Quartz Crystal Unit - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0