NSN 5955-00-945-3492

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-945-3492

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 31.5 and 32.5
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
10.33333 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.008/+0.008
Frequency Stability In Percent:
-0.0005/+0.0005
Controlled Reference Temp:
85.0 degrees celsius
Operable Tempurature Range:
-55.0/+80.0 degrees celsius
Holder Cover Material:
Metal
Operating Tempurature Range:
+80.0/+90.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Pating

brive Level Rating.

Between 2.0 milliwatts and 3.0 milliwatts

NSN 5955-00-945-3492

Quartz Crystal Unit - Page 2 of 2



Eroau	onev	Toloranco	Ear (Inoratina	Tempurature	In Parcent:
rrequ	lency	i olei ance	roi v	operanny	rempurature	in Fercent.

-0.002/+0.002

Equivalent Resistance Value In Ohms:

22.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A059a0