

View Online at <https://aerobasegroup.com/nsn/5955-00-951-9024>

Overall Length:

1.023 inches

Terminal Length:

0.238 inches

Overall Width:

0.757 inches

Body Length:

0.775 inches

Body Width:

0.725 inches

Body Thickness:

0.317 inches

Overall Thickness:

0.352 inches

Terminal Diameter:

0.050 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

Between 32.0 and 31.5 and 32.5

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

8.500 megahertz

Frequency Tolerance At Reference Temperature In Percent:

-0.008/+0.008

Frequency Stability In Percent:

-0.0005/+0.0005

Controlled Reference Temp:

85.0 degrees celsius

Operable Temperature Range:

-55.0/+80.0 degrees celsius

Holder Cover Material:

Metal

Operating Temperature Range:

+80.0/+90.0 degrees celsius

Center To Center Distance Between Terminals:

0.486 inches

Drive Level Rating:

Between 5.0 milliwatts and 4.0 milliwatts and 6.0 milliwatts

Frequency Tolerance For Operating Temperature In Percent:

-0.002/+0.002

Equivalent Resistance Value In Ohms:

24.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A059a0