NSN 5955-00-952-5729

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-952-5729

| Overall Length: |
|---|
| 1.023 inches |
| Terminal Length: |
| Between 0.223 inches and 0.248 inches |
| Overall Width: |
| 0.757 inches |
| Body Length: |
| 0.775 inches |
| Body Width: |
| 0.725 inches |
| Body Thickness: |
| 0.317 inches |
| Overall Thickness: |
| 0.352 inches |
| Terminal Diameter: |
| Between 0.048 inches and 0.052 inches |
| Mode Of Oscillation: |
| Third overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 7.0 |
| Specified Frequency: |
| 38.28889 megahertz |
| Frequency Tolerance At Reference Tempurature In Percent: |
| -0.007/+0.007 |
| Frequency Stability In Percent: |
| -0.00025/+0.00025 |
| Controlled Reference Temp: |
| 75.0 degrees celsius |
| Operable Tempurature Range: |
| -55.0/+90.0 degrees celsius |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| +70.0/+80.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.478 mils and 0.494 centimeters |
| Drive Level Rating: |
| Between 0.8 milliwatts and 1.2 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |

-0.001/+0.001

NSN 5955-00-952-5729

Quartz Crystal Unit - Page 2 of 2

Fiig: A059a0



| Equivalent Resistance Value In Ohms: |
|--|
| 40.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: |
| 31349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No. |