NSN 5955-00-957-2565

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-957-2565

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
•
38.34074 megahertz
•
38.34074 megahertz
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals:
38.34074 megahertz Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters

-0.001/+0.001

NSN 5955-00-957-2565

Quartz Crystal Unit - Page 2 of 2



Equivalent Resistance \	Value Ir	Ohms:
--------------------------------	----------	-------

40.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A059a0