NSN 5955-00-976-5244

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-976-5244

Over	all I	en	ath:
~~	an L	-611	иит.

Between 1.010 inches and 1.050 inches

Overall Height:

Between 1.000 inches and 1.015 inches

Overall Width:

Between 1.010 inches and 1.050 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+5.0/+500.0

Vibration Resistance Amplitude:

10.0 gravitational units

Shock Resistance Rating In Gravitational Units:

15.0

Operating Tempurature Range:

-54.0/+105.0 degrees celsius

Average Life Rating:

2500.0

Average Life Measurement:

Hours

Average Life Rating In Hours:

2500.0

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

65000.0 feet

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

3.24 kilohertz operating channel

Connection Type And Location:

Wire lead terminals bottom

Connection Contact Type And Quantity:

3 wire lead terminals external

NSN 5955-00-976-5244

Noncrystal Controlled Oscillator - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200