# NSN 5955-00-978-4839

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-978-4839

Between 0.015 inches and 0.019 inches

#### Mode Of Oscillation:

Fifth overtone and third overtone

**Circuit Resonance:** 

Series resonance

### Shunt Capacitance In Picofarads:

3.75

#### Specified Frequency:

101.3667 megahertz

### Holder Cover Material:

Metal or glass

#### **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius and -55.0/+125.0 degrees celsius

#### **Center To Center Distance Between Terminals:**

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

Between 1.0 milliwatts and 1.5 milliwatts

#### Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005 and -0.0010/+0.0010

#### **Equivalent Resistance Value In Ohms:**

60.0

#### Style Designator:

Tube type, 4 wire leads

Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 5955-00-978-4839

Quartz Crystal Unit - Page 2 of 2

**Fiig:** A059a0

