## NSN 5955-00-978-6349

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-978-6349

0
Overall Length:
0.775 inches
Terminal Length:
Between 1.500 inches and 1.525 inches
Overall Width:
0.757 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.030 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 19.5 and 20.5
Specified Frequency:
453.650 kilohertz
Holder Cover Material:
Metal or glass
Operating Tempurature Range:
Operating Tempurature Range: -0.1/+60.0 degrees celsius
-0.1/+60.0 degrees celsius
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals:
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals:  0.469 mils and 0.531 centimeters
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals:  0.469 mils and 0.531 centimeters  Drive Level Rating:
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals:  0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent:
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100  Equivalent Resistance Value In Ohms: 8000.0
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100  Equivalent Resistance Value In Ohms: 8000.0  Style Designator:
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100  Equivalent Resistance Value In Ohms: 8000.0  Style Designator: Tube type, 4 wire leads
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100  Equivalent Resistance Value In Ohms: 8000.0  Style Designator:  Tube type, 4 wire leads  Shelf Life:
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100  Equivalent Resistance Value In Ohms: 8000.0  Style Designator: Tube type, 4 wire leads  Shelf Life: N/a
-0.1/+60.0 degrees celsius  Center To Center Distance Between Terminals: 0.469 mils and 0.531 centimeters  Drive Level Rating:  Between 1.6 milliwatts and 2.4 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.010/+0.010 and -0.100/+0.100  Equivalent Resistance Value In Ohms: 8000.0  Style Designator:  Tube type, 4 wire leads  Shelf Life:

Yes - demil/mli

## NSN 5955-00-978-6349

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0