NSN 5955-00-985-1998

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-985-1998

Overall Length:						
1.023 inches						
Terminal Length:						
Between 0.223 inches and 0.248 inches						
Overall Width:						
0.757 inches						
Body Length:						
0.775 inches						
Body Width:						
0.725 inches						
Body Thickness:						
0.317 inches						
Overall Thickness:						
0.352 inches						
Terminal Diameter:						
Between 0.048 inches and 0.052 inches						
Mode Of Oscillation:						
Fundamental						
Circuit Resonance:						
Antiresonance						
Load Capacitance In Picofarads:						
Between 31.5 and 32.5						
Shunt Capacitance In Picofarads:						
7.0						
Specified Frequency:						
3.800 megahertz						
Frequency Tolerance At Reference Tempurature In Percent:						
-0.007/+0.007						
Frequency Stability In Percent:						
-0.0005/+0.0005						
Controlled Reference Temp:						
75.0 degrees celsius						
Operable Tempurature Range:						
-55.0/+90.0 degrees celsius						
Holder Cover Material:						
Metal						
Operating Tempurature Range:						
+70.0/+80.0 degrees celsius						
Center To Center Distance Between Terminals:						
0.478 mils and 0.494 centimeters						
Drive Level Rating:						

Dilve Level Mating

Between 4.0 milliwatts and 6.0 milliwatts

NSN 5955-00-985-1998

Quartz Crystal Unit - Page 2 of 2



Frequency	Tolerance	For	Operating	Tempurature I	n Percent:

-0.002/+0.002

Equivalent Resistance Value In Ohms:

75.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A059a0