## NSN 5955-00-992-9591

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-992-9591

Overall Length:
1.023 inches
Terminal Length:
0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
10.0
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
opecined i requency.
3.200 megahertz
3.200 megahertz
3.200 megahertz  Frequency Stability In Percent:
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp:
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range:
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:  Metal or glass
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range:
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range: +30.0/+40.0 degrees celsius
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range: +30.0/+40.0 degrees celsius  Center To Center Distance Between Terminals:
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range: +30.0/+40.0 degrees celsius  Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters
3.200 megahertz  Frequency Stability In Percent: -0.0005/+0.0005  Controlled Reference Temp: 35.0 degrees celsius  Operable Tempurature Range: -0.1/+85.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range: +30.0/+40.0 degrees celsius  Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters  Drive Level Rating:

## NSN 5955-00-992-9591

Quartz Crystal Unit - Page 2 of 2



250.0

**Style Designator:** 

Tube body, wire leads

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0