# NSN 5955-00-992-9618

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-992-9618

## **Overall Length:**

Between 0.998 inches and 1.023 inches

## **Terminal Length:**

Between 0.223 inches and 0.248 inches

## **Overall Width:**

0.757 inches

### **Body Length:**

0.775 inches

### **Body Width:**

0.725 inches

### Body Thickness:

0.317 inches

### **Overall Thickness:**

0.352 inches

### **Terminal Diameter:**

Between 0.048 inches and 0.052 inches

## Mode Of Oscillation:

Fundamental

### **Circuit Resonance:**

Antiresonance

## Load Capacitance In Picofarads:

10.0

## Shunt Capacitance In Picofarads:

7.0

## Specified Frequency:

340.000 kilohertz

# Frequency Tolerance At Reference Tempurature In Percent:

-0.005/+0.005

## Frequency Stability In Percent:

-0.0005/+0.0005

## **Controlled Reference Temp:**

25.0 degrees celsius

## **Operable Tempurature Range:**

+0.0/+85.0 degrees celsius

# Holder Cover Material:

Metal

# **Operating Tempurature Range:**

+20.0/+30.0 degrees celsius

# Center To Center Distance Between Terminals:

0.478 mils and 0.494 centimeters

## **Drive Level Rating:**

2.0 milliwatts

# NSN 5955-00-992-9618

Quartz Crystal Unit - Page 2 of 2



Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001

## Equivalent Resistance Value In Ohms:

3500.0

Style Designator:

Oval body, pin terminals

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0