NSN 5955-00-999-4839

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-999-4839

Overall Length:0.530 inchesFerninal Length:Between 1.500 inches and 1.525 inchesOverall Width:0.435 inchesBody Width:0.432 inchesBody Width:0.402 inchesBody Thickness:0.150 inchesOverall Thickness:0.150 inchesOverall Thickness:0.183 inchesFerninal Diameter:Between 0.015 inches and 0.019 inchesMode Of Oscillation:Third overtone and fifth overtoneCircuit ResonanceSeries resonanceShurt Capacitance In Picofarads:3.5Specified Frequency:26.830 megahertzHolder Cover Material:Metal or glassOperating Tempurature Range:-3.00/+55.0 degrees celsiusCenter To Center Distance Between Terminals:-10.202/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:-0.002-0.002/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:-0.002Shelf Life:N/aUnit of Measure:	View Online at https://aerobasegroup.com/nsn/5955-00-999-4839
Terminal Length: Between 1.500 inches and 1.525 inches Overall Width: 0.435 inches Body Width: 0.432 inches Body Width: 0.402 inches Body Thickness: 0.150 inches Overall Thickness: 0.150 inches Overall Thickness: 0.183 inches Terminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -3.0.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Sheif Life: <	Overall Length:
Between 1.500 inches and 1.525 inches Overall Width: 0.435 inches Body Width: 0.402 inches Body Thickness: 0.103 inches Overall Thickness: 0.183 inches Terminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Netal or glass Operating Tempurature Range: -3.0.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Syle Designator: Tube type, 4 wire leads Sheff Life: N/a	0.530 inches
Overall Width:0.435 inchesBody Width:0.402 inchesBody Thickness:0.150 inchesOverall Thickness:0.150 inchesOverall Thickness:0.183 inchesTerminal Diameter:Between 0.015 inches and 0.019 inchesMode Of Oscillation:Third overtone and fifth overtoneCircuit Resonance:Series resonanceShunt Capacitance In Picofarads:3.5Specified Frequency:26.830 megahertzHolder Cover Material:Metal or glassOperating Tempurature Range:-3.0.0/+55.0 degrees celsiusCenter To Center Distance Between Terminals:0.184 mils and 0.200 centimetersDrive Level Rating:Between 1.6 milliwatts and 2.4 milliwattsFrequency Tolerance For Operating Tempurature In Percent:-0.002/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:-0.002-0.002/+0.002 and -0.007/+0.007Fuivale Life:N/aVina Uppe, 4 wire leadsShelf Life:N/aViaDit of Measure:Staff Life:N/a <tr< td=""><td>Terminal Length:</td></tr<>	Terminal Length:
0.435 inches Body Width: 0.402 inches Body Thickness: 0.150 inches Overall Thickness: 0.150 inches Overall Thickness: 0.183 inches Terminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: 0.184 mils and 0.200 centimeters Dive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: 0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 4.0.0 Style Designator: Tube type, 4 wire leads Sheff Life: N/a Unit Of Measure:	Between 1.500 inches and 1.525 inches
Body Width: 0.402 inches Body Thickness: 0.150 inches Overall Thickness: 0.183 inches Terminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -3.0.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Syle Designator: Tube type, 4 wire leads Sheff Life: N/a Unit Of Measure:	Overall Width:
0.402 inchesBody Thickness:0.150 inchesOverall Thickness:0.183 inchesTerminal Diameter:Between 0.015 inches and 0.019 inchesMode Of Oscillation:Third overtone and fifth overtoneCircuit Resonance:Series resonanceShunt Capacitance In Picofarads:3.5Specified Frequency:26.830 megahertzHolder Cover Material:Metal or glassOperating Tempurature Range:-3.0./+55.0 degrees celsiusCenter To Center Distance Between Terminals:0.184 mils and 0.200 centimetersDrive Level Rating:-0.002/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:40.0Style Designator:Tube type, 4 wire leadsShelf Life:N/aUnit Of Measure:	0.435 inches
Body Thickness: 0.150 inches Overall Thickness: 0.183 inches Terminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Body Width:
0.150 inchesOverall Thickness:0.183 inchesTerminal Diameter:Between 0.015 inches and 0.019 inchesMode Of Oscillation:Third overtone and fifth overtoneCircuit Resonance:Series resonanceShunt Capacitance In Picofarads:3.5Specified Frequency:26.830 megahertzHolder Cover Material:Metal or glassOperating Tempurature Range:-3.0./+55.0 degrees celsiusCenter To Center Distance Between Terminals:O184 mils and 0.200 centimetersDrive Level Rating:Between 1.6 milliwatts and 2.4 milliwattsFrequency Tolerance For Operating Tempurature In Percent:-0.002/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:40.0Siyle Designator:Tube type, 4 wire leadsShelf Life:N/aUnit Of Measure:-	0.402 inches
Overall Thickness:0.183 inchesTerminal Diameter:Between 0.015 inches and 0.019 inchesMode Of Oscillation:Third overtone and fifth overtoneCircuit Resonance:Series resonanceShunt Capacitance In Picofarads:3.5Specified Frequency:26.830 megahertzHolder Cover Material:Metal or glassOperating Tempurature Range:-30.0/+55.0 degrees celsiusCenter To Center Distance Between Terminals:0.184 mils and 0.200 centimetersDrive Level Rating:Between 1.6 milliwatts and 2.4 milliwattsFrequency Tolerance For Operating Tempurature In Percent:-0.002/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:40.0Style Designator:Tube type, 4 wire leadsShelf Life:N/aUnit Of Measure:	Body Thickness:
 0.183 inches 7erminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -3.0.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure: 	0.150 inches
Terminal Diameter: Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -3.0.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Overall Thickness:
Between 0.015 inches and 0.019 inches Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	0.183 inches
Mode Of Oscillation: Third overtone and fifth overtone Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: 0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Terminal Diameter:
Third overtone and fifth overtoneCircuit Resonance:Series resonanceShunt Capacitance In Picofarads:3.5Specified Frequency:26.830 megahertzHolder Cover Material:Metal or glassOperating Tempurature Range:-30.0/+55.0 degrees celsiusCenter To Center Distance Between Terminals:0.184 mils and 0.200 centimetersDrive Level Rating:Between 1.6 milliwatts and 2.4 milliwattsFrequency Tolerance For Operating Tempurature In Percent:0.002/+0.002 and -0.007/+0.007Equivalent Resistance Value In Ohms:40.0Style Designator:Tube type, 4 wire leadsShelf Life:N/aUnit Of Measure:	Between 0.015 inches and 0.019 inches
Circuit Resonance: Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Mode Of Oscillation:
Series resonance Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Third overtone and fifth overtone
Shunt Capacitance In Picofarads: 3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Circuit Resonance:
3.5 Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Series resonance
Specified Frequency: 26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Shunt Capacitance In Picofarads:
26.830 megahertz Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	3.5
Holder Cover Material: Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Specified Frequency:
Metal or glass Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	26.830 megahertz
<pre>Operating Tempurature Range: -30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:</pre>	Holder Cover Material:
-30.0/+55.0 degrees celsius Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Metal or glass
Center To Center Distance Between Terminals: 0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Operating Tempurature Range:
0.184 mils and 0.200 centimeters Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	-30.0/+55.0 degrees celsius
Drive Level Rating: Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Center To Center Distance Between Terminals:
Between 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	0.184 mils and 0.200 centimeters
Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Drive Level Rating:
-0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Between 1.6 milliwatts and 2.4 milliwatts
Equivalent Resistance Value In Ohms: 40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Frequency Tolerance For Operating Tempurature In Percent:
40.0 Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	-0.002/+0.002 and -0.007/+0.007
Style Designator: Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	Equivalent Resistance Value In Ohms:
Tube type, 4 wire leads Shelf Life: N/a Unit Of Measure:	40.0
Shelf Life: N/a Unit Of Measure:	Style Designator:
N/a Unit Of Measure:	Tube type, 4 wire leads
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:

Yes - demil/mli

NSN 5955-00-999-4839

Quartz Crystal Unit - Page 2 of 2

Fiig: A059a0

