

NSN 5955-01-004-7098 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-004-7098 **Overall Length:** 0.790 inches **Overall Height:** 0.466 inches **Overall Width:** 0.490 inches **Vibration Resistance Range In Hertz:** +10.0/+2000.0 **Vibration Resistance Amplitude:** 15.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** Not rated **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Circuit Construction Type:** Solid state **Frequency Per Channel:** 4.0 megahertz operating channel **Frequency Adjustment Type:** Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:**

Signal Voltage Rating Per Channel:

4.000 volts interstage preset

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

NSN 5955-01-004-7098

Noncrystal Controlled Oscillator - Page 2 of 2



Connection	Type	And	Location:
------------	------	-----	-----------

Wire lead terminals bottom

Connection Contact Type And Quantity:

7 wire lead terminals external

External Dc Operating Voltage In Volts:

5.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200