## NSN 5955-01-005-8928

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-005-8928
Overall Length:
Between 5.980 inches and 6.020 inches
Overall Height:
Between 4.520 inches and 4.560 inches
Overall Width:
1.060 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
50.0
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Average Life Rating:
38800.0
Average Life Measurement:
Hours
Average Life Rating In Hours:
38800.0
Basic Shape Style:
Rectangular or square
Identification Designator:
154048-94117
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
2.2 megahertz operating channel and 15.8 megahertz operating channel
Frequency Adjustment Type:
Stepped
Individual Step Frequency:
2.2 megahertz and 15.8 megahertz
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:

Not rated

**Signal Voltage Rating Per Channel:** 

1.000 volts output and 13.000 volts output

## NSN 5955-01-005-8928

Crystal Controlled Oscillator - Page 2 of 2



Overall (	Gain:
-----------	-------

Not rated

Impedance Rating Per Channel:

50.000 ohms operating channel

**Maximum Continuous Operating Time In Hours:** 

Not rated

**Connection Type And Location:** 

Receptacle, coaxial bottom

**Connection Contact Type And Quantity:** 

2 terminal block w/screw external

**External Dc Operating Voltage In Volts:** 

11.6 2nd voltage err-100 and 12.4 2nd voltage err-100

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

Yes - demil/mli

Fiig:

A32200