NSN 5955-01-013-4763

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-013-4763 **Overall Length:** 0.680 inches **Overall Diameter:** Between 0.335 inches and 0.370 inches **Vibration Resistance Range In Hertz:** +5.0/+55.0 **Vibration Resistance Amplitude:** 0.06 inches total excursion **Shock Resistance Rating In Gravitational Units:** 30.0 **Average Life Measurement:** Not rated **Basic Shape Style:** Cylindrical **Maximum Operating Altitude Rating:** 10000.000 feet **Inclosure Type: Encased Installation Design:** Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 10.0 megahertz operating channel Signal Voltage Rating Per Channel: 5.000 volts input and 39.000 volts output **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Wire lead terminals bottom **Connection Contact Type And Quantity:** 3 wire lead terminals external **External Dc Operating Voltage In Volts:** 5.0 single voltage **Fsc Application Data:** Test sets, electronic systems, except specially designed Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5955-01-013-4763

Noncrystal Controlled Oscillator - Page 2 of 2



Fiig:

A32200