NSN 5955-01-013-8563

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-01-013-8563



Overall Length: 1.500 inches **Overall Height:** 0.855 inches **Overall Width:** 1.500 inches **Environmental Protection:** Salt spray resistant **Vibration Resistance Range In Hertz:** +5.0/+55.0 **Vibration Resistance Amplitude:** 0.6 inches total excursion **Shock Resistance Rating In Gravitational Units:** 18.0 **Operating Tempurature Range:** -0.0/+75.0 degrees celsius **Average Life Rating:** 50000.0 **Average Life Measurement:** Hours **Average Life Rating In Hours:** 50000.0 **Basic Shape Style:** Rectangular or square **Identification Designator:** Hj12-29p-16484 **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased Installation Design: **Circuit Construction Type:** Solid state Frequency Per Channel: 50.0 megahertz operating channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: 5.000 volts interstage preset

NSN 5955-01-013-8563 Crystal Controlled Oscillator - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
50000.0
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
4 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200