## NSN 5955-01-014-5848

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-01-014-5848



**Overall Length:** 1.530 inches **Overall Height:** 0.320 inches **Overall Width:** 1.530 inches **Shock Resistance Rating In Gravitational Units:** 45.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Rating:** 2000.0 **Average Life Measurement: Average Life Rating In Hours:** 2000.0 **End Application:** Inertial navigation system, an/asn 109 **Basic Shape Style:** Rectangular or square **Identification Designator:** 779754-1-06481 **Maximum Operating Altitude Rating:** 70000.000 feet **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 13.824 megahertz operating channel Frequency Adjustment Type: Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 250.0 milliwatts input Signal Voltage Rating Per Channel: 5.000 volts input

## NSN 5955-01-014-5848 Crystal Controlled Oscillator - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
3.0 milliseconds
Connection Type And Location:
Connector, plug bottom
Connection Contact Type And Quantity:
6 connector, plug external
External Dc Operating Voltage In Volts:
5.0 single voltage
Fsc Application Data:
Inertial measurement unit. 683420-23
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A32200