NSN 5955-01-018-4620

Quartz Crystal Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-018-4620

Overall Length:
Between 0.515 inches and 0.535 inches
Terminal Length:
Between 1.470 inches and 1.530 inches
Overall Width:
Between 0.418 inches and 0.438 inches
Overall Thickness:
Between 0.166 inches and 0.186 inches
Terminal Diameter:
Between 0.007 inches and 0.027 inches
Mode Of Oscillation:
Seventh overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
Between 3.5 and 4.5
Specified Frequency:
150.875 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-50.0/+75.0 degrees celsius
-50.0/+75.0 degrees celsius Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator: Oval body, wire leads w/hold down wire
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator: Oval body, wire leads w/hold down wire Shelf Life:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator: Oval body, wire leads w/hold down wire Shelf Life: N/a
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator: Oval body, wire leads w/hold down wire Shelf Life: N/a
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator: Oval body, wire leads w/hold down wire Shelf Life: N/a Unit Of Measure:
Center To Center Distance Between Terminals: 0.182 mils and 0.202 centimeters Drive Level Rating: 4.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: 100.0 Style Designator: Oval body, wire leads w/hold down wire Shelf Life: N/a Unit Of Measure: Demilitarization: