## NSN 5955-01-018-6941

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-018-6941

Overall Length: 1.023 inches Terminal Length: Between 0.223 inches and 0.248 inches Overall Width: 0.757 inches Body Length: Between 0.750 inches and 0.775 inches Overall Thickness: 0.352 inches Terminal Diameter:
Terminal Length: Between 0.223 inches and 0.248 inches Overall Width: 0.757 inches Body Length: Between 0.750 inches and 0.775 inches Overall Thickness: 0.352 inches
Between 0.223 inches and 0.248 inches Overall Width: 0.757 inches Body Length: Between 0.750 inches and 0.775 inches Overall Thickness: 0.352 inches
Overall Width: 0.757 inches Body Length: Between 0.750 inches and 0.775 inches Overall Thickness: 0.352 inches
0.757 inches <b>Body Length:</b> Between 0.750 inches and 0.775 inches <b>Overall Thickness:</b> 0.352 inches
Body Length: Between 0.750 inches and 0.775 inches Overall Thickness: 0.352 inches
Between 0.750 inches and 0.775 inches Overall Thickness: 0.352 inches
Overall Thickness: 0.352 inches
0.352 inches
Terminal Diameter:
רפוווווומו שומוווכוכו.
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
3.0
Specified Frequency:
70.000 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.0002/+0.0002
Frequency Stability In Percent:
-0.00025/+0.00025
Controlled Reference Temp:
75.0 degrees celsius
Operable Tempurature Range:
-55.0/+90.0 degrees celsius
Holder Cover Material:
Metal
Operating Tempurature Range:
+70.0/+80.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 0.8 milliwatts and 1.2 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.0002/+0.0002
Equivalent Resistance Value In Ohms:
40.0
Style Designator:
Oval body, pin terminals

## NSN 5955-01-018-6941

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0

