Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-019-3962

Overall Length:
2.275 inches
Overall Height:
0.352 inches
Overall Width:
0.757 inches
Environmental Protection:
Moisture proof and salt spray resistant and shock resistant and vibration
Vibration Resistance Range In Hertz:
+10.0/+500.0
Vibration Resistance Amplitude:
10.0 gravitational units
Shock Resistance Rating In Gravitational Units:
100.0
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
70000.0 feet
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
41.0 megahertz operating channel
Shock Pulse Duration Time:
6.0 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
3 pin external
External Dc Operating Voltage In Volts:
10.0 single voltage

Crystal Controlled Oscillator - Page 2 of 2



Fsc Application Data:

Piezoelectric crystals

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200