## NSN 5955-01-021-7156

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-021-7156 **Overall Length:** 19.000 inches **Overall Height:** 7.000 inches **Overall Width:** 15.250 inches **Vibration Resistance Range In Hertz:** Not rated **Individual Section Quantity: Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** Not rated **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 1308-98-012-4655 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Manual Installation Design: Top of cabinet/counter **Control Type:** Local **Circuit Construction Type:** Any acceptable Frequency Per Channel: 200.0 hertz 2nd operating channel err-100 Frequency Adjustment Type: Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 200.0 watts output

Signal Voltage Rating Per Channel:

400.000 volts interstage preset

## NSN 5955-01-021-7156 Crystal Controlled Oscillator - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
800.000 ohms 5th output channel err-100
Distortion Type And Percent:
1.0 frequency
Indicator Device Type And Quantity:
2 meter
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, power rear
Operating Ac Frequency In Hertz:
60.0 4th voltage
Connection Contact Type And Quantity:
4 receptacle, power external
External Ac Operating Voltage In Volts:
250.0 4th voltage
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A32200