NSN 5955-01-023-5509

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-023-5509

Overa	11 1	۸n	ath	٠.
Overa	II L	.en	uti	1:

Between 0.220 inches and 0.265 inches

Terminal Length:

0.500 inches

Diameter:

Between 0.310 inches and 0.330 inches

Overall Diameter:

Between 0.350 inches and 0.380 inches

Terminal Diameter:

Between 0.016 inches and 0.019 inches

Mode Of Oscillation:

Fifth overtone

Circuit Resonance:

Series resonance

Shunt Capacitance In Picofarads:

Between 2.3 and 3.2

Specified Frequency:

97.373737 megahertz

Frequency Tolerance At Reference Tempurature In Percent:

-0.001/+0.001

Frequency Stability In Percent:

-0.001/+0.001

Controlled Reference Temp:

65.0 degrees celsius

Operable Tempurature Range:

-30.0/+80.0 degrees celsius

Holder Cover Material:

Metal

Operating Tempurature Range:

+60.0/+70.0 degrees celsius

Center To Center Distance Between Terminals:

0.190 mils and 0.210 centimeters

Drive Level Rating:

Between 0.4 milliwatts and 0.6 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001

Equivalent Resistance Value In Ohms:

55.0

Style Designator:

Hat type, 3 wire leads

Shelf Life:

N/a

NSN 5955-01-023-5509

Quartz Crystal Unit - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A059a0