Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-027-7352

Overall Length:
2.500 inches
Overall Height:
0.500 inches
Overall Width:
2.000 inches
Environmental Protection:
Fungus proof and moisture proof and salt spray resistant
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Vibration Resistance Amplitude:
10.0 gravitational units
Operating Tempurature Range:
-30.0/+100.0 degrees celsius
Average Life Rating:
87648.0
Average Life Measurement:
Hours
Average Life Rating In Hours:
87648.0
Basic Shape Style:
Rectangular or square
Identification Designator:
508933-5-31550
Phase Shift Angle In Deg:
0.005 output to input
Maximum Operating Altitude Rating:
10000.0 feet
Inclosure Type:
Encased
Operating Control Method:
Manual
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
1.5625 kilohertz output channel
Frequency Adjustment Type:
Continuous

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

5.0 2nd voltage err-100 and 5.5 2nd voltage err-100

Criticality Code Justification:

Feat

Special Features:

Used on poseidon material

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200