NSN 5955-01-029-0864

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-029-0864

view Online at https://aerobasegroup.com/hsh/osss-01-025-0004
Overall Length:
0.530 inches
Terminal Length:
Between 0.500 inches and 0.830 inches
Overall Width:
0.435 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
Between 0.016 inches and 0.019 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
3.5
Specified Frequency:
24.5892 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+90.0 degrees celsius and -55.0/+105.0 degrees celsius
Center To Center Distance Between Terminals:
0.184 mils and 0.200 centimeters
Drive Level Rating:
Between 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.002/+0.002 and -0.003/+0.003
Equivalent Resistance Value In Ohms:
40.0
Style Designator:
Oval body, wire leads w/hold down wire
Test Data Document:
81349-mil-c-3098/57 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

Specification Data:

81349-mil-c-3098/53 government specification

N/a

NSN 5955-01-029-0864

Quartz Crystal Unit - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A059a0