# NSN 5955-01-030-3043

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-030-3043

## **Overall Length:**

0.778 inches

#### **Terminal Length:**

Between 0.223 inches and 0.248 inches

#### **Overall Width:**

0.435 inches

#### **Body Length:**

0.530 inches

#### **Body Width:**

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

#### Terminal Diameter:

Between 0.038 inches and 0.042 inches

#### Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

#### Load Capacitance In Picofarads:

Between 29.5 and 30.5

#### Shunt Capacitance In Picofarads:

7.0

## Specified Frequency:

9.7524 megahertz

## Holder Cover Material:

Metal

## **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius

# Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

## **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

# Equivalent Resistance Value In Ohms:

30.0

#### Style Designator:

Oval body, pin terminals

#### **Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5955-01-030-3043

Quartz Crystal Unit - Page 2 of 2



**Specification Data:** 

81349-milc3098/62c government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0