## NSN 5955-01-030-4816

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-030-4816 **Overall Length:** 1.000 inches **Overall Height:** 0.760 inches **Overall Width:** 1.000 inches **Vibration Resistance Range In Hertz:** +10.0/+500.0 **Individual Section Quantity: Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 200.0 **Operating Tempurature Range:** -0.0/+75.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 723102-1-05869 **Maximum Operating Altitude Rating:** 12000.0 feet **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 20.0 megahertz operating channel err-100 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** Not rated **Overall Gain:** Not rated Impedance Rating Per Channel:

Not rated

## NSN 5955-01-030-4816

Crystal Controlled Oscillator - Page 2 of 2



Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 microseconds
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
4 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A32200