NSN 5955-01-033-2078

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-033-2078

Overall Length:
0.778 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.435 inches
Body Length:
0.530 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
Between 0.038 inches and 0.042 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
4.450 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Center To Center Distance Between Terminals:
0.184 mils and 0.200 centimeters
Drive Level Rating:
Between 4.0 milliwatts and 6.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.005/+0.005
Equivalent Resistance Value In Ohms:
50.0
Style Designator:
Oval body, pin terminals
Test Data Document:
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-milc3098/63 government specification

NSN 5955-01-033-2078

Quartz Crystal Unit - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0