NSN 5955-01-034-9371

Quartz Crystal Unit - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5955-01-034-9371

Overall Length:
0.260 inches
Terminal Length:
1.000 inches
Diameter:
Between 0.305 inches and 0.335 inches
Overall Diameter:
0.370 inches
Terminal Diameter:
Between 0.016 inches and 0.019 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
Between 3.8 and 5.3
Specified Frequency:
112.6042 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
+70.0/+80.0 degrees celsius
Center To Center Distance Between Terminals:
v
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating:
Center To Center Distance Between Terminals: 0.200 inches
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator: Hat type, 3 wire leads
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator: Hat type, 3 wire leads Shelf Life:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a Unit Of Measure:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a Unit Of Measure:
Center To Center Distance Between Terminals: 0.200 inches Drive Level Rating: 0.5 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.0005/+0.0005 Equivalent Resistance Value In Ohms: 60.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a Unit Of Measure: Demilitarization: