Crystal Controlled Oscillator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-039-6908

| ~ | |
|----|--|
| | verall Length: |
| | 0.0 millimeters |
| | verall Height: |
| | 0.0 millimeters |
| 0 | verall Width: |
| 35 | 0.0 millimeters |
| 0 | perating Tempurature Range: |
| -1 | 0.0/+55.0 degrees celsius |
| ٩ | verage Life Measurement: |
| No | ot rated |
| Ba | asic Shape Style: |
| Re | ectangular or square |
| ld | entification Designator: |
| 0- | 009-51984 |
| In | closure Type: |
| Er | ncased |
| In | stallation Design: |
| M | odule |
| Ci | rcuit Construction Type: |
| So | olid state |
| Fr | equency Per Channel: |
| 7. | 913 megahertz operating channel |
| 0 | verall Gain: |
| 50 | 0.0 milliamperes |
| Im | pedance Rating Per Channel: |
| 10 | 0.000 ohms operating channel |
| С | onnection Type And Location: |
| Sc | older lug bottom |
| С | onnection Contact Type And Quantity: |
| 4 | solder lug external |
| E | tternal Dc Operating Voltage In Volts: |
| 12 | 2.0 single voltage |
| | nelf Life: |
| N/ | a |
| U | nit Of Measure: |
| | |
| De | emilitarization: |
| N | |
| Fi | ig: |
| A | 32200 |