## NSN 5955-01-042-5210

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-042-5210

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 31.5 and 32.5
Shunt Capacitance In Picofarads:
9.0
Specified Frequency:
14.8600 megahertz
Frequency Stability In Percent:
-0.00005/+0.00005
Holder Cover Material:
Metal
Operating Tempurature Range:
-10.0/+60.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 1.0 milliwatts and 2.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.001/+0.001
Equivalent Resistance Value In Ohms:
13.0
Style Designator:
Oval body, pin terminals

## NSN 5955-01-042-5210

Quartz Crystal Unit - Page 2 of 2



## **Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

SI.	امد	fΙ	ife	

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A059a0