## NSN 5955-01-045-5342

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-045-5342

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
1.228 megahertz
Holder Cover Material:
Metal
Metal  Operating Tempurature Range:
Operating Tempurature Range:
Operating Tempurature Range: -55.0/+105.0 degrees celsius
Operating Tempurature Range: -55.0/+105.0 degrees celsius Center To Center Distance Between Terminals:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.003/+0.003
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.003/+0.003  Equivalent Resistance Value In Ohms:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.003/+0.003  Equivalent Resistance Value In Ohms: 100.0
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.003/+0.003  Equivalent Resistance Value In Ohms: 100.0  Style Designator:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.003/+0.003  Equivalent Resistance Value In Ohms: 100.0  Style Designator: Oval body, pin terminals

## NSN 5955-01-045-5342

Quartz Crystal Unit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A059a0