NSN 5955-01-048-2695

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-048-2695

Overall Length:
Between 0.998 inches and 1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.812 inches
Body Length:
0.775 inches
Body Width:
0.687 inches
Body Thickness:
0.282 inches
Overall Thickness:
0.407 inches
Terminal Diameter:
Between 0.048 inches and 0.051 inches
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
75.0
Shunt Capacitance In Picofarads:
Shunt Capacitance In Picofarads: 7.0
•
7.0
7.0 Specified Frequency:
7.0 Specified Frequency: 5.000 megahertz
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material:
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range:
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals:
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating:
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 40.0 microwatts
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 40.0 microwatts Equivalent Resistance Value In Ohms:
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 40.0 microwatts Equivalent Resistance Value In Ohms: 40.0
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 40.0 microwatts Equivalent Resistance Value In Ohms: 40.0 Special Features:
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 40.0 microwatts Equivalent Resistance Value In Ohms: 40.0 Special Features: Can also be holder style hc-27/u
7.0 Specified Frequency: 5.000 megahertz Holder Cover Material: Metal Operating Tempurature Range: +80.0/+90.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 40.0 microwatts Equivalent Resistance Value In Ohms: 40.0 Special Features: Can also be holder style hc-27/u Style Designator:

--

Unit Of Measure:

NSN 5955-01-048-2695

Quartz Crystal Unit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A059a0