NSN 5955-01-056-8037

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-056-8037

| Overa | II Le | ngth: |
|-------|-------|-------|
| | | |

Between 0.220 inches and 0.265 inches

Terminal Length:

Between 0.500 inches and 0.830 inches

Diameter:

Between 0.310 inches and 0.330 inches

Overall Diameter:

Between 0.350 inches and 0.380 inches

Terminal Diameter:

Between 0.016 inches and 0.019 inches

Mode Of Oscillation:

Fifth overtone and third overtone

Circuit Resonance:

Series resonance

Shunt Capacitance In Picofarads:

Between 2.3 and 3.2

Specified Frequency:

98.737373 megahertz

Holder Cover Material:

Metal

Operating Tempurature Range:

+60.0/+70.0 degrees celsius

End Application:

Jetds type no. An/tsm-15, test set, crystal unit, quartz

Center To Center Distance Between Terminals:

0.190 mils and 0.210 centimeters

Drive Level Rating:

Between 0.16 milliwatts and 0.50 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001 and -0.0015/+0.0015

Equivalent Resistance Value In Ohms:

55.0

Style Designator:

Hat type, 3 wire leads

Fsc Application Data:

Miscellaneous communication equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5955-01-056-8037

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0