

View Online at <https://aerobasegroup.com/nsn/5955-01-056-8040>

**Overall Length:**

Between 0.220 inches and 0.265 inches

**Terminal Length:**

Between 0.500 inches and 0.830 inches

**Diameter:**

Between 0.310 inches and 0.330 inches

**Overall Diameter:**

Between 0.350 inches and 0.380 inches

**Terminal Diameter:**

Between 0.016 inches and 0.019 inches

**Mode Of Oscillation:**

Fifth overtone and third overtone

**Circuit Resonance:**

Series resonance

**Shunt Capacitance In Picofarads:**

Between 2.3 and 3.2

**Specified Frequency:**

97.676767 megahertz

**Frequency Tolerance At Reference Temperature In Percent:**

-0.00075/+0.00075

**Controlled Reference Temp:**

65.0 degrees celsius

**Operable Temperature Range:**

-30.0/+80.0 degrees celsius

**Holder Cover Material:**

Metal

**Operating Temperature Range:**

+60.0/+70.0 degrees celsius

**Center To Center Distance Between Terminals:**

0.190 mils and 0.210 centimeters

**Drive Level Rating:**

500.0 microwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.001/+0.001 and -0.0015/+0.0015

**Equivalent Resistance Value In Ohms:**

55.0

**Style Designator:**

Hat type, 3 wire leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A059a0