## NSN 5955-01-056-8043

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-056-8043

Overa	II Le	ngth:

Between 0.220 inches and 0.265 inches

**Terminal Length:** 

Between 0.500 inches and 0.830 inches

Diameter:

Between 0.310 inches and 0.330 inches

**Overall Diameter:** 

Between 0.350 inches and 0.380 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

**Mode Of Oscillation:** 

Fifth overtone and third overtone

**Circuit Resonance:** 

Series resonance

**Shunt Capacitance In Picofarads:** 

Between 2.3 and 3.2

**Specified Frequency:** 

87.557345 megahertz

**Frequency Tolerance At Reference Tempurature In Percent:** 

-0.00075/+0.00075

**Controlled Reference Temp:** 

65.0 degrees celsius

**Operable Tempurature Range:** 

-30.0/+80.0 degrees celsius

**Holder Cover Material:** 

Metal

**Operating Tempurature Range:** 

+60.0/+70.0 degrees celsius

**Center To Center Distance Between Terminals:** 

0.190 mils and 0.210 centimeters

**Drive Level Rating:** 

500.0 microwatts

**Frequency Tolerance For Operating Tempurature In Percent:** 

-0.001/+0.001 and -0.0015/+0.0015

**Equivalent Resistance Value In Ohms:** 

55.0

Style Designator:

Hat type, 3 wire leads

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5955-01-056-8043

Quartz Crystal Unit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A059a0