NSN 5955-01-062-9442

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-062-9442 **Overall Length:** 5.691 inches **Overall Height:** 3.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -20.0/+65.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 3253688-10001 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encapsulated **Installation Design:** Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 3.5 megahertz output channel **Attenuation In Decibels: Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** Not rated **Overall Gain:**

Not rated Impedance Rating Per Channel: 50.000 ohms 2nd output channel err-100 **Maximum Continuous Operating Time In Hours:** Not rated

NSN 5955-01-062-9442

Noncrystal Controlled Oscillator - Page 2 of 2



Connection Type And Location:

Receptacle, coaxial front and receptacle, coaxial front and receptacle, power front

Connection Contact Type And Quantity:

1 receptacle, coaxial internal and 1 receptacle, coaxial internal and 6 receptacle, power internal

External Dc Operating Voltage In Volts:

-14.5 2nd voltage err-100 and -15.5 2nd voltage err-100

Special Features:

Has an internal oven and over-voltage protection, case rf shielded

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32200