NSN 5955-01-071-6309

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-071-6309

Overall Length:
Between 1.970 inches and 2.000 inches
Overall Height:
Between 0.980 inches and 1.000 inches
Overall Width:
Between 1.970 inches and 2.000 inches
Environmental Protection:
Moisture proof and salt spray resistant and shock resistant and vibration
Shock Resistance Rating In Gravitational Units:
40.0
Operating Tempurature Range:
-32.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Manual
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
53.0 megahertz operating channel
Frequency Adjustment Type:
Continuous
Shock Pulse Duration Time:
6.0 milliseconds
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
5 liters of liquid nitrogen drain
External Dc Operating Voltage In Volts:
15.0 single voltage
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5955-01-071-6309

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200