Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-071-6309

## **Overall Length:** Between 1.970 inches and 2.000 inches **Overall Height:** Between 0.980 inches and 1.000 inches Overall Width: Between 1.970 inches and 2.000 inches **Environmental Protection:** Moisture proof and salt spray resistant and shock resistant and vibration Shock Resistance Rating In Gravitational Units: 40.0 **Operating Tempurature Range:** -32.0/+85.0 degrees celsius Average Life Measurement: Not rated **Basic Shape Style:** Rectangular or square Inclosure Type: Encased **Operating Control Method:** Manual Installation Design: Module **Control Type:** Local **Circuit Construction Type:** Solid state **Frequency Per Channel:** 53.0 megahertz operating channel **Frequency Adjustment Type:** Continuous **Shock Pulse Duration Time:** 6.0 milliseconds **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 5 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 15.0 single voltage Shelf Life: N/a Unit Of Measure: ---

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200