## NSN 5955-01-074-4325

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-074-4325 **Overall Length:** 3.000 inches **Overall Height:** 2.000 inches **Overall Width:** 1.641 inches **Environmental Protection:** Fungus proof and moisture proof and salt spray resistant **Vibration Resistance Range In Hertz:** +10.0/+55.0 **Operating Tempurature Range:** -46.0/+71.0 degrees celsius **Average Life Measurement:** Hours **Basic Shape Style:** Rectangular or square **Identification Designator:** 140208-1-24930 **Maximum Operating Altitude Rating:** 10000.000 feet **Inclosure Type:** Encased **Operating Control Method:** Manual Installation Design: Mechanical **Control Type:** Local **Circuit Construction Type:** Solid state Frequency Per Channel: 8.7 gigahertz operating channel and 9.3 gigahertz operating channel Frequency Adjustment Type: Continuous **Variation Frequency Rating In Decibels:** Signal Voltage Rating Per Channel: 1.000 millivolts input Impedance Rating Per Channel:

50.000 ohms operating channel

**Connection Type And Location:** 

Receptacle, coaxial bottom and solder lug rear

## NSN 5955-01-074-4325

Noncrystal Controlled Oscillator - Page 2 of 2



## **Connection Contact Type And Quantity:**

1 receptacle, coaxial internal and 1 solder lug external

## **External Dc Operating Voltage In Volts:**

9.0 single voltage and 11.5 single voltage

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A32200