NSN 5955-01-074-6222

Vibration Resistance Range In Hertz:

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-074-6222

G
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-25.0/+71.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
Sm-a-934937-80063
Maximum Operating Altitude Rating:
50000.0 feet
Inclosure Type:
Encased
Installation Design:
Drawer
Circuit Construction Type:
Solid state
Frequency Per Channel:
Not rated
Attenuation In Decibels:
90.0
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
24.000 volts input
Overall Gain:
10.0 decibels
Impedance Rating Per Channel:
180.000 ohms input channel err-100
Distortion Type And Percent:
10.0 frequency
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Integral cord w/power plug front
External Dc Operating Voltage In Volts:
24.0 single voltage
Shelf Life:

N/a

NSN 5955-01-074-6222

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200